

AIR

P. TOT.
kw 4.5 - 9

P. NOM.
kw 4.3 - 8.1



NATURAL 9

150 kg - 20 ~ kg Pellet



- Porta in ghisa
- Top in ghisa
- Pannelli laterali in acciaio
- Ampia visione della fiamma
- Sensori di sicurezza
- Superficie di scambio termico in ghisa

- Cast iron door
- Cast iron top
- Steel side panels
- Wide view of the flame
- Security sensors
- Heat-Exchange surface in cast iron

- Porte en fonte
- Haut en fonte
- Panneaux latéraux en acier
- Large vue de la flamme
- Capteurs de sécurité
- Surface d'échange thermique en fonte

- Porta en fundició
- Top en fundició
- Paneles laterales en acero
- Amplia visió de la llama
- Sensores de seguridad
- Superficie de intercambio de calor en fundició

RDS SYSTEM
RHS SYSTEM
FIREX
GPRS
CLEAR
ECO START
TIMER
ASH
SILENT
ECO-FRIENDLY
MONEY-SAVING
RADIO WAVE
K PROBE



TOUCH
display

DUAL
technology

NATURAL
convection

HERMETIC
system

zero
philosophy

Bianco
White
Blanc
Blanco

Nero
Black
Noir
Negro



108 cm
52 cm
46 cm

